



Nylon Cable Glands (G Thread)

Nylon G

Deeflex



Applications

Used for fixing cables and provide the effective protection against dust, water, oil and acid in the fields of electrical and electronic technologies, machines, telecommunications, wireless networking ODU's, power supplies, switches, junction boxes, solar PV modules, Inverters, lightings, displays, traffics, signals, surveillance cameras, measurements, sensors, plant engineering, installation and other instruments. Innovative design for the Seal and Clamp, wide clamping range, strong resistance against the tensile strength and thus it can protect cables effectively.

Characteristics

- Material: UL-certified Halogen-free PA66, flammability 94V-2 for A,C,F parts (UL file: E223722).
- Thread System: According to JIS B 0204.
- Seal & Washer: Oil resistant NBR, weather resistant EPDM or Natural Rubber for B,D parts.
- Standard Color: Grey RAL7035, black RAL9005, other colors are available on request.
- IP Protection : Up to IP68 (used together with Washer within its cable range).
- Operation Temp.: Static:-40C to 100C, short-term: 120C. Dynamic:-20C to 80C, short-term:100C.
- Installation: Cables can be directly inserted into the hole of the same size thread and then fix it with the Locknut.

Specifications

Thread	Cable Range		AG (C1) (mm)	GL(C2) (mm)	H (mm)	Spanner (mm)
	Min. (mm)	Max. (mm)				
PCNG14AX	3	6.5	13.1	8	22	15/16
PCNG14BX	2	5	13.1	8	22	15/16
PCNG38AX	4	8	16.6	15	26	19
PCNG38BX	2	6	16.6	15	26	19
PCNG12AX	6	12	20.9	13	30	24
PCNG12BX	5	9	20.9	13	30	24
PCNG34X	13	18	26.4	15	37	33
PCNG1AX	18	25	33.2	16	40	41
PCNG1BX	13	20	33.2	16	40	41
PCNG114AX	18	25	41.9	18	40	46/42
PCNG114BX	13	20	41.9	18	40	46/42
PCNG112AX	22	32	47.8	15	48	52/53
PCNG112BX	20	26	47.8	15	48	52/53
PCNG2AX	37	44	59.6	15	50	64
PCNG2BX	29	35	59.6	15	50	64

***P/N (x) for Black Color use B, Grey Color use G